

NRC Publications Archive Archives des publications du CNRC

Fire event timeline for basement fire scenarios in single family dwellings

Lougheed, Gary; Su, Joseph; Bénichou, Nouredine; Bwalya, Alex; Taber, Bruce; Leroux, Patrice

NRC Publications Archive Record / Notice des Archives des publications du CNRC :

<https://nrc-publications.canada.ca/eng/view/object/?id=ebccd852-c975-446b-9aea-bcee06064c81>

<https://publications-cnrc.canada.ca/fra/voir/objet/?id=ebccd852-c975-446b-9aea-bcee06064c81>

Access and use of this website and the material on it are subject to the Terms and Conditions set forth at

<https://nrc-publications.canada.ca/eng/copyright>

READ THESE TERMS AND CONDITIONS CAREFULLY BEFORE USING THIS WEBSITE.

L'accès à ce site Web et l'utilisation de son contenu sont assujettis aux conditions présentées dans le site






<https://publications-cnrc.canada.ca/fra/droits>







LISEZ CES CONDITIONS ATTENTIVEMENT AVANT D'UTILISER CE SITE WEB.

Questions? Contact the NRC Publications Archive team at

PublicationsArchive-ArchivesPublications@nrc-cnrc.gc.ca. If you wish to email the authors directly, please see the first page of the publication for their contact information.

Vous avez des questions? Nous pouvons vous aider. Pour communiquer directement avec un auteur, consultez la première page de la revue dans laquelle son article a été publié afin de trouver ses coordonnées. Si vous n'arrivez pas à les repérer, communiquez avec nous à PublicationsArchive-ArchivesPublications@nrc-cnrc.gc.ca.








Smoke Alarm Responses										
Smoke alarm location	Basement fire room	1 st storey		2 nd storey corridor		2 nd storey bedroom (open)		2 nd storey bedroom (closed)		
type	I	P 2	I 3	P 4	I 5	P 6	I 9	P 10	I 7	P 8
Tests with open basement doorway										
Test UF-01	-	40	75	85	125	135	140	150	200	205
Test UF-03	-	48	58	73	123	133	143	143	218	228
Test UF-04	-	30	65	85	115	130	160	225	230	250
Test UF-05	-	45	40	55	130	145	155	165	245	275
Test UF-06	-	45	75	85	115	125	130	200	230	255
Test UF-06R	-	38	58	78	113	123	138	163	198	223
Test UF-06RR	-	43	73	78	128	138	143	153	223	248
Test UF-07	-	50	40	55	110	130	130	145	190	210
Tests with closed basement doorway										
Test UF-02	-	42	72	97	172	182	212	n.a.	427	541
Test UF-08	-	50	85	95	205	205	220	210	515	515
Test UF-09	-	44	79	89	179	179	209	204	479	459

Smoke Alarm Responses										
<ul style="list-style-type: none"> Smoke alarms in the basement detected the fire in 30 – 50 s – Average 43 s. Activation time delayed for non-interconnected smoke alarms 										
Open Basement Door (average response time)										
<ul style="list-style-type: none"> 67 s main floor; 126 s second floor corridor; 198 s bedroom with open door; 264 s bedroom with closed door. 										
Closed Basement Door (average response time)										
<ul style="list-style-type: none"> 86 s main floor; 187 s the second floor corridor; 206 s bedroom with open door; 489 s bedroom with closed door. 										




Tenability Analysis										
<ul style="list-style-type: none"> Untenable conditions <ul style="list-style-type: none"> Smoke obscuration (optical density measurements) Toxic, asphyxiant gases (CO/CO₂/O₂ measurements) Heat (temperature measurements) 										



Tenability Analysis – estimation of time to untenable conditions


- Depending on many factors
 - Fire characteristics and house geometry
 - Endpoints for tenability analysis (incapacitation used)
 - Occupant characteristics, activities, susceptibility, thresholds/tenability limits
 - Each occupant likely to have a different time
- Tenability limit/threshold values used
 - Smoke obscuration: optical density (OD) = 2 m^{-1}
 - CO/CO₂ or heat exposure: fractional effective dose approach
 - FED = 1 for a healthy adult of average susceptibility
 - FED = 0.3 for a more susceptible person

14 Jan 2009, 11:00 AM



Structural Response of the Test Assemblies

- Temperatures
- Flame penetration
- Deflections



Primary Mode of Floor Failure

Solid wood joist assemblies: subfloor failure (burn through)



ARC-CARC


DOI 10.1002/for

ATC-CATC

MS 104-100000, Georgia, Mar 16, 2014

ARC-CARC

HJ 618 Barrenish - Longo Ltd © 2019

© 2004 Blackwell Publishing Ltd, *Journal of Internal Medicine* 255: 103–110

of the University, Chicago, Ill. 60607.

ARC-CARC

- U.S. DEPARTMENT OF JUSTICE, January 10, 1940

Key Findings (continued)

NRC-CNRC

▪ Limited tests with a closed door to the basement

3 assemblies: solid wood joist, wood I-joist, metal-web wood truss

- Reduced fire size in the basement
- Slowed the transport of combustion products from the basement to the upper storeys
- Delayed the time to reach tenability limits for occupants on upper storeys
- Delayed the times for the test floor assemblies to reach structural failure
- Metal-web wood truss assembly failed before tenability limits were reached in open areas on upper storeys

NRC-CNRC, 11/11/2010, 11/11/2010

Key Findings (continued)

NRC-CNRC

▪ All tests

- The time to reach failure for the engineered assemblies was shorter than for the solid wood joist assemblies
- Untenable conditions were not reached, for the duration of the tests, in the second-storey bedroom where the door to the bedroom was kept closed
- Results support the code requirement for working interconnected smoke alarms on each level of a house to alert occupants as early as possible in the event of a fire
- Results reinforce the importance of continued public education on home fire safety, fire emergency preparedness and immediate evacuation upon a fire alert

NRC-CNRC, 11/11/2010, 11/11/2010

Further Studies

NRC-CNRC

- Consortium project (2008-2010) – protected floor assemblies in basement fire scenarios
 - engineered floor systems protected by gypsum board, sprinkler or other measures
 - Impact of the protection measures on fire performance and tenability conditions
- Fire Performance of Houses Phase 2 (starting 2011)
 - Innovative wall assemblies for single-family houses

NRC-CNRC, 11/11/2010, 11/11/2010

Acknowledgments

NRC-CNRC

- Project partners (Phase 1):
 - Canada Mortgage and Housing Corporation
 - Canadian Automatic Sprinkler Association
 - Canadian Wood Council
 - Cement Association of Canada
 - City of Calgary
 - FPInnovations - Forintek Division
 - North American Insulation Manufacturers Association
 - Ontario Ministry of Community Safety and Correctional Services/Office of the Fire Marshal
 - Ontario Ministry of Municipal Affairs and Housing
 - Wood I-Joist Manufacturers Association

NRC-CNRC, 11/11/2010, 11/11/2010