



NRC Publications Archive Archives des publications du CNRC

Survey of Vibration Periods in Multi-Storey Buildings

Rainer, J. H.

For the publisher's version, please access the DOI link below./ Pour consulter la version de l'éditeur, utilisez le lien DOI ci-dessous.

Publisher's version / Version de l'éditeur:

<https://doi.org/10.4224/20338435>

Technical Note (National Research Council of Canada. Division of Building Research), 1974-04-01

NRC Publications Record / Notice d'Archives des publications de CNRC:

<https://nrc-publications.canada.ca/eng/view/object/?id=ae624f39-6850-4789-b7ce-588de2c78261>

<https://publications-cnrc.canada.ca/fra/voir/objet/?id=ae624f39-6850-4789-b7ce-588de2c78261>

Access and use of this website and the material on it are subject to the Terms and Conditions set forth at

<https://nrc-publications.canada.ca/eng/copyright>

READ THESE TERMS AND CONDITIONS CAREFULLY BEFORE USING THIS WEBSITE.

L'accès à ce site Web et l'utilisation de son contenu sont assujettis aux conditions présentées dans le site

<https://publications-cnrc.canada.ca/fra/droits>

LISEZ CES CONDITIONS ATTENTIVEMENT AVANT D'UTILISER CE SITE WEB.

Questions? Contact the NRC Publications Archive team at

PublicationsArchive-ArchivesPublications@nrc-cnrc.gc.ca. If you wish to email the authors directly, please see the first page of the publication for their contact information.

Vous avez des questions? Nous pouvons vous aider. Pour communiquer directement avec un auteur, consultez la première page de la revue dans laquelle son article a été publié afin de trouver ses coordonnées. Si vous n'arrivez pas à les repérer, communiquez avec nous à PublicationsArchive-ArchivesPublications@nrc-cnrc.gc.ca.



National Research
Council Canada

Conseil national de
recherches Canada

Canada



NATIONAL RESEARCH COUNCIL OF CANADA

DIVISION OF BUILDING RESEARCH

No.

589

TECHNICAL NOTE

DIRECTOR'S OFFICE COPY

NOT TO BE REMOVED FROM ROOM 201

PREPARED BY J.H. Rainer

CHECKED BY T.D.N.

APPROVED BY L.W.G.

DATE April 1974

PREPARED FOR Record Purposes

SUBJECT SURVEY OF VIBRATION PERIODS IN MULTI-STOREY BUILDINGS

A program of measuring the natural periods of buildings was undertaken for the purpose of checking and evaluating the adequacy of formulae for calculating the natural periods given in the National Building Code of Canada. This note describes the method of measuring the natural periods and gives the results obtained in the various buildings. The full evaluation of the results will be carried out in future publications.

The natural periods are a unique characteristic of a building. Besides their obvious use in design calculations, the initial natural periods of a building are useful to know should some future event such as an earthquake, blast or planned alteration change the stiffness or mass properties of the building. Such changes would then be reflected in shifts in the natural periods of the structure.

EXPERIMENTAL METHOD

The natural period of the building was determined from the ambient vibrations monitored near the top of the building. Generally two "Larson" servo-drive accelerometers (5 V/g sensitivity) were placed at opposite ends of the building. The direction of the sensitive axis was oriented so that by adding the signals either translational motion or rotational (torsion) motion was obtained. The signal from the accelerometers was amplified (generally with 40 dB) and filtered. The low-pass filter setting was chosen, by trial and error, just above the natural frequency. The signals were then added and displayed on a Hewlett-Packard strip chart recorder. Before each recording run, the entire electronic assembly was calibrated so that when the accelerometers were facing each other essentially zero output was obtained.

The experimental procedure proved quite satisfactory and enabled a complete set of measurements for one building to be taken in one to two hours. A diagram of the experimental setup is shown in Fig. 1, and a sample of a typical record obtained is shown in Fig. 2. Along with the ambient vibration results, man-excited vibrations were also recorded.

RESULTS

The results of the measurements of natural periods of buildings are presented in Table 1. Each building is given a code letter which can be employed in referencing the experimental data in possible future publications. "Transverse" is generally the short direction, and "longitudinal" the long direction of the building. Where ambiguity might arise the approximate compass orientation of building motion is given.

In addition to the ambient vibration results, the natural frequency was also determined from the decay curve of man-excited oscillations. These values are identified by an asterisk (*).

The accuracy of the results depends essentially on the speed control of the recorder and on the adjustment of the electronic instruments. Since a system calibration was carried out before each test, the possible source of error originating in the electronics is effectively eliminated. The speed of the recorder is generally controlled to 2 - 3%, and the results can, therefore, be expected to have that level of accuracy.

ACKNOWLEDGEMENT

Permission to take the measurements and cooperation of the owners and management of the buildings is acknowledged. Special thanks are due to the Ontario Housing Authority, Standard Life Assurance Co., Glenview Investments Ltd., Campeau Corporation, Minto Construction Ltd., Carleton University, Holiday Inn (Downtown), and Skyline Hotel. The active assistance and cooperation of the staff of J. Stuart Hall and Associates Ltd., and of J. Adjelian and Associates, both consulting engineers in Ottawa, is also gratefully acknowledged.

TABLE 1

AMBIENT VIBRATION PERIODS OF BUILDINGS IN OTTAWA

Code Letter	Length ft	Width ft	Total Height ft	No. of Storeys N	Bldg. Type	Date of Measurement	Transverse		Longitudinal		Torsion	
							T ₁ Sec.	T ₂ Sec.	T ₁ Sec.	T ₂ Sec.	T ₁ Sec.	T ₂ Sec.
A	182.5	55.3	206.0	24	C - S	Oct. 24 - 25, 1973	1.61		1.15		1.56	
E	154.0	57.2	231	27	C - S	Oct. 24 - 25, 1973	1.51* 1.49	0.37	1.37	0.38	1.48	0.39
C	131	50.6	196.2	22	S - C	Oct. 24 - 25, 1973	1.27	0.34	1.20* 1.18	0.33	0.98	0.29
D	131	50.6	196.2	22	S - C	Oct. 24 - 25, 1973	1.27	0.325	1.19* 1.16	0.316	0.98	0.29
E(+)	219	54.9	231.8 (193.5)	24 (20)	C - S	Oct. 24 - 25, 1973	1.39	0.375	1.01* 1.02	0.32	1.26 1.35	0.36
F	131.3	94.0	249.5	27	C - S	Nov. 1973	1.32	0.405	1.24	0.375	1.32	0.40
G	171.5	54.2	265.3	27	C - S	Nov. 1973	1.46	0.38	1.17	--	1.09	--
H	101.7	83.0	263.5	23	C - S	Nov. 1973	(E-W) 1.67* 1.66	0.420	(N-S) 1.48	0.36	0.970	0.25
J	180.0	110.0	359.6 (339.9)	30 (29)	S - F	Nov. 1973	(E-W) 3.48	1.20	(N-S) 4.20	1.4	4.82	1.53
K					S - C	Oct. 1972			1.01			
L	112.5	88.0	118.6 (109.0)	13 (12)	M	Jan. 16, 1974	(E-W) 0.415		(N-S) 0.44			

() Dimensions in parentheses are those measured from ground level.

(+) Somewhat irregular in plan dimension.

Building types: C - S: Reinforced concrete shear wall
 S - F: Steel frame and braced core
 S - C: Steel frame and concrete shear walls
 M : Masonry




FIGURE 1
EXPERIMENTAL SET-UP




FIGURE 2
TYPICAL VIBRATION RECORDS